

MANUFACTURERS MOTOR VEHICLE SPECIFICATIONS

METRIC (U.S. Customary)

Passenger Car

1987

Manufacturer CHRYSLER MOTORS	Car Line DODGE ARIES	
Mailing Address DETROIT, MICHIGAN 48288	Issued JUNE 20, 1986	Revised

Questions concerning these specifications should be directed to the manufacturer whose address is shown above.

The information contained herein is prepared, distributed by, and is solely the responsibility of the automobile manufacturing company to whose products it relates. This specification form was developed by the automobile manufacturing companies under the auspices of the Motor Vehicle Manufacturers Association of the United States, Inc.

The General Specifications herein are those in effect at date of compilation and are subject to change without notice by the manufacturer.

MVMA Specifications Form

Passenger Car

METRIC (U.S. Customary)

Table of Contents

1	Car Models
2	Power Teams
3-6	Engine
4	Lubrication System
4	Diesel Information
5	Cooling System
6	Fuel System
7	Vehicle Emission Control
7	Exhaust System
8-10	Transmission, Axles and Shafts
11	Suspension-Front and Rear
12-13	Brakes
13	Tires and Wheels
14-15	Steering
15-16	Electrical
17	Body – Miscellaneous Information.
18	Restraint System
18	Frame
18	Glass
19	Convenience Equipment
20-22	Car and Body Dimensions
23	Vehicle Fiducial Marks
24	Lamps and Headlamps
25	Vehicle Mass (Weight)
26	Optional Equipment Differential Mass (Weight)
27-33	Car and Body Dimensions Definitions - Key Sheets
34	Index

NOTE:

1. This form uses both SI metric units and U.S. Customary units. The metric unit of measure is presented first, and the U.S. Customary unit follows in parentheses.
2. **UNLESS OTHERWISE INDICATED:**
 - a. Specifications apply to standard models without optional equipment. Significant deviations are noted.
 - b. Nominal design dimensions are used throughout these specifications.
 - c. All linear dimensions are in millimeters (inches), and all mass (weight) specifications are in kilograms (pounds).
3. The General Specifications herein are those in effect at date of completion and are subject to change without notice by the manufacturer.
4. Additional Car and Body Dimensions (based in part on SAE J1100 "Motor Vehicle Dimensions") may be available from the manufacturer.

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line DODGE ARIES

Model Year 1987

Issued 6 - 20 - 86

Revised (a) _____

Car Models

Model Description & Drive (FWD/RWD)	Introduction Date	Make, Car Line, Series, Body Type (Mfr's Model Code)	No. of Designated Seating Positions (Front/Rear)	Max. Trunk/Cargo Load-Kilograms (Pounds)
ARIES-FWD	SEPT. 1986			
2-DOOR SEDAN		DL21	5(2/3)	52(115)
4-DOOR SEDAN		DL41	5(2/3)	52(115)
ARIES LE-FWD	SEPT. 1986			
2-DOOR SEDAN		DM21	5(2/3)	52(115)
4-DOOR SEDAN		DM41	5(2/3)	52(115)
2-SEAT WAGON		DM45	5(2/3)	68(150)

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised (●)

Power Teams (Indicate whether standard or optional)

SAE J1349 Net bhp (brake horsepower) and net torque corrected to 77°F/25°C
 and 29.61 in. Hg/100 kPa atmospheric pressure.

SERIES AVAILABILITY	ENGINE					E x h a u s t S/D	TRANSMISSION TRANSAXLE	AXLE RATIO (std. first)
	Displ. Liters (in. ³)	Carb. (Barrel, Fl, etc.)	Compr. Ratio	SAE Net at RPM				
				kW (bhp)	Torque N-m (lb. ft.)			
STD.	2.2L (135) EDF	EFI	9.5	72 (97) @ 5200	165 (122) @ 3200	S	MANUAL 5-Speed	2.51
				AUTOMATIC			2.78(a), 3.02(c)	
OPT. M	2.5L (153) EDM	EFI	9.0	75 (100) @ 4800	180 (133) @ 2800	S	AUTOMATIC	3.02, 3.22 (b)

(a) Not available for 45

(b) Police Package

(c) Police package and 45

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•) _____

Engine description/Carb.
 Engine Code

2.2L (135.0 in³)
EFI, EDF

2.5L (153.0 in³)
EFI, EDM

ENGINE - GENERAL

Type & description (inline, V, angle, flat, location, front, mid, rear; transverse, longitudinal, sohc, dohc, ohv, hemi, wedge, pre-chamber, etc.)	Four-cylinder, in-line, SOHC, canted, front, transverse	
Manufacturer	Chrysler	
No. of Cylinders	Four	
Bore	87.5 (3.44)	
Stroke (C/L to C/L)	92.0 (3.62)	
Bore spacing (C/L to C/L)	96.0 (3.78)	
Cylinder block mat'l. & mass kg (lbs.) (machined)	Cast iron 35.79 (78.9)	Cast Iron 39.42 (86.9)
Cylinder block deck height	237.8 (9.36)	249.8 (9.83)
Cylinder block length	418 (16.46)	
Deck clearance (minimum) (above or below block)	0.00	
Cylinder head material & mass kg (lbs.)	Aluminum 9.71 (21.4)	
Cylinder head volume (cm ³)	48.5 -51.5	
Cylinder liner material	n.a.	
Head gasket thickness (compressed)	1.78 (.070)	
Minimum combustion chamber total volume (cm ³)	Clearance volume: 65.31	Clearance Volume: 73.815
Cyl. no. system (front to rear)*	Right to left as installed in car 1, 2, 3, 4	
Firing order	1, 3, 4, 2	
Intake manifold mat'l. & mass [kg(lbs.)]**	Aluminum 2.62 (5.8)	
Exhaust manifold mat'l. & mass [kg(lbs.)]**	Cast iron 6.23 (13.7)	
Recommended fuel (leaded, unleaded, diesel)	Regular unleaded	
Fuel antiknock index $\frac{R + M}{2}$	87 octane or higher	
Total dressed engine mass (wt) dry***	128.64 (283.6)	140.57 (309.9)

Engine - Pistons

Material & mass, g (weight, oz.) piston only	Aluminum	
	440 (15.7)	430 (15.1)

Engine - Camshaft

Location	Overhead	
Material & mass kg (weight, lbs.)	Hardenable cast iron 2.92 (6.4)	
Drive type	Chain/belt	Belt
	Width/pitch	Width: 24.7 (0.972) (a)
		23.8 (0.937) (a)

*Rear of engine - drive takeoff. View from drive takeoff end to determine left & right side of engine.

**Finished state

***Dressed engine mass (weight) includes the following: starter, alternator, manifolds, water pump, engine-mounted emission controls, drive belts, oil filter, right engine mount, and throttle controls as required

(a) Pitch: 9.52 (0.375)

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)
Chassis and Body Dimensions

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised(*)

Engine description/Carb.

Engine Code

2.2L (135.0 in.3)
EFI, EDF

2.5L (153.0 in.3)
EFI, EDM

Engine - Valve System

Hydraulic lifters (std., opt., n.a.)

Std.

Valves

Number intake/exhaust

4/4

Head O.D. intake/exhaust

40.6 mm. / 35.4 mm.

Engine - Connecting Rods

Material & Mass [kg., (weight lbs.)]

Forged steel 0.63 (1.4)

Forged steel 0.67 (1.5)

Engine - Crankshaft

Material & Mass [kg., (weight lbs.)]

Nodular iron 15.19 (33.5)

Forged steel 16.52 (36.4)

End thrust taken by bearing (no.)

Three

Number of main bearings

Five

Seal (material, one,

Front

One piece

two piece design, etc.)

Rear

One piece

Engine - Lubrication System

Normal oil pressure [kPa (psi) at eng. rpm]

25 - 80 psi @ 3000

Type of intake (floating, stationary)

Stationary

Oil filter system (full flow, part, other)

Full flow

Capacity of c/case, less filter-refill-L (qt.)

3.8 (4)

Engine - Diesel Information

Diesel engine manufacturer

Glow plug, current drain at 0° F

Injector

Type

nozzle

Opening pres. [kPa (psi)]

Pre-chamber design

Fuel inj.

Manufacturer

pump

Type

Fuel inj. pump drive (belt, chain, gear)

Supplementary vacuum source (type)

Fuel heater (yes/no)

Water separator description (std., opt.)

Turbo manufacturer

Oil cooler type (oil to engine coolant;

oil to ambient air)

Oil filter

Engine - Intake System

Turbo - charger - Manufacturer

Super - charger - manufacturer

Charge cooler

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised (•) _____

Engine Description/Carb.

Engine Code

2.2L (135.0 in³) EFI, EDF, 2.5 L (153.0 in. ³) EFI, EDM

W/O AC

W/AC

Engine - Cooling System

Coolant recovery system (std., opt., n.a.)		Standard	
Coolant fill location (rad., bottle)		Bottle	
Radiator cap relief valve pressure (kPa (psi))		96-124 (14-18)	
Circulation thermostat	Type (choke, bypass)	Choke, Pellet Operated	
	Starts to open at °C(°F)	90.6 (195)	
Water Pump	Type (centrifugal, other)	Centrifugal	
	GPM 1000 pump RPM	-	
	Number of pumps	One	
	Drive (V-belt, other)	Multi-Groove Belt	
	Bearing type	Integral Ball Bearing	
	Impeller material	Steel	
	Housing material	Cast Aluminum	
By-pass recirculation (type (inter., ext.))		external	
Cooling System	With heater - L(qt.)	8.5 (9.0)	
	With air cond. - L(qt.)	8.5 (9.0)	
Capacity	Opt. equip. [specify - L(qt.)]	--	
Water jackets full length of cyl. (yes, no)		Yes	
Water all around cylinder (yes, no)		No	
Water jackets open at head face (yes, no)			
Radiator Core	Std., A/C, HD		
	Type (cross-flow, etc.)	Cross-Flow	
	Construction (fin&tube, mechanical, braze, etc.)	Tube & Fin Spacer, Soldered, 1 Row	
	Material, mass[kg(wt., lbs.)] (a)	(b) (c)	(b) (d),
	Width	533.4 (21.0)	
	Height	387.6 (15.26)	
	Thickness	17.8 (0.7)	
	Fins per inch	13	15 man., 16 or 20 auto.
Radiator end tank material		Nylon 66	
Fan	Std., elec., opt.	Electric	
	Number of blades & type (flex, solid, material)	2-Blade Metal	
	Diameter & projected width	315(12.4)/33(1.3)	360 (14.2) / 46 (1.8)
	Ratio (fan to crankshaft rev.)	-	
	Fan cutout type	Electric Motor	
	Drive type (direct, remote)	-	
	RPM at idle (elec.)	1815	1790
	Motor rating (wattage) (elec.)	65	130
	Motor switch (type & loc.) (elec.)	Thermistor, Water Box & A/C	
	Switch point (temp., press.) (elec.)	99 °C (210° F) (Low Speed); 110 °C (230° F) (High Speed)	
	Fan shroud (material)	Metal	

(a) Mass (weight) shown is for assembly as purchased.

(b) Copper-brass

(c) 4.22 (9.3) EDF w/man. trans., 4.63 (10.2) all auto. trans.

(d) 4.55 (10.0) EDF w/man. trans., 4.74 (10.5) 41 w/EDF & auto. trans., 5.03 (11.1) EDM & 45 w/EDF & auto. trans.

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line DODGE ARIES
 Model Year 1987 Issued 6-20-86 Revised (•) _____

Engine Description/Carb.
 Engine Code

2.2L (135.0 in ³) / EFI EDF	2.5L (153.0 in ³) / EFI EDM
--	--

Engine - Fuel System (See supplemental page for details of Fuel Injection, Supercharger, Turbocharger, etc. if used)

Induction type: carb., fuel inj. sys., etc.			electronic fuel injection
Carburetor	Mfr.		Bosch or Holly
	Choke (type)		none
	Idle spd. rpm (spec. neutral or drive and propane if used)	Manual	
		Automatic	700
Idle A/F mix			--
Fuel Injection	Point of injection (no.)		throttle body (1)
	Constant,pulse, flow		pulse
	Control (electronic, mech.)		electronic
	System pressure [kPa (psi)]		100 (14.5)
Intake manifold heat control (exhaust or water thermostatic or fixed)			water
Air cleaner type	Standard		oil-wetted paper element
	optional		--
Fuel pump	Type (elec. or mech.)		electric
	Location (eng., tank)		in fuel tank
	Pressure range [kPa (psi)]		116-262 @12V & 15.0 PSI(a)

Fuel Tank

Capacity (refill L (gallons))		53 (14.0)
Location (describe)		forward of axle
Attachment		Galv. or terne plated strap to floor pan
Material & mass [kg (weight [lbs.])]		terne plated steel 9.34 (20.6)
Filler pipe	Location & material	external, right rear quarter panel; lead dipped steel
	Connection to tank	rubber grommet
Fuel line (material)		duplex-coated steel
Fuel hose (material)		fuel resistant rubber
Return line (material)		duplex-coated steel
Vapor line (material)		terne plated steel
Extended range tank	Opt., n. a.	
	Capacity [L (gallons)]	
	Location & material	
	Attachment	
Auxiliary tank	Opt., n. a.	
	Capacity [L (gallons)]	
	Location & material	
	Attachment	
	Selector switch or valve	
	Separate fill	

(a) Flow Range (lbs./hr.)@ nominal regulated pressure.

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised(*)

Engine Description/Carb.
 Engine Code

2.2L(135.0in³)
EFI
EDF

2.5L (153.0 in.³)
EFI
EDM

Vehicle Emission Control

Exhaust Emission Control	Type (air injection, eng. modifications)		(a)
	Air injection	Pump or pulse	pulse
		Driven by	exhaust pressure
		Air distribution (head, manifold, etc.)	single point
		Point of entry	exhaust manifold collector
	Exhaust Gas Recirc- ulation	Type (controlled flow, open oriface, other)	controlled flow
		Exhaust source	manifold collector
		Point of exhaust inj. (spacer, carb., manif., etc.)	intake manifold
	Catalytic Converter	Type	3 - Way + oxidation
		Number of	one
Location(s)		below exhaust manifold	
Volume [L9in. ³]		1.23(75) 3WC + 0.74(45)ox.	
	Substrate type	monolithic	
Crankcase Emission Control	Type (ventilates to atmosphere, induction system, other)		closed induction system
	Energy source (manifold, vacuum, carburetor, other)		manifold vacuum
	Discharges (to intake manif., other)		intake manifold
	Air inlet (breather cap, other)		air cleaner
Evapora- tive emis- sion control Electronic system	Vapor vented to (crank- case, canister, other)	Fuel tank	canister
		Carburetor	--
	Vapor storage position		canister
	Closed loop (yes/no)		yes - hot engine
	Open loop (yes/no)		yes - cold engine

Engine - Exhaust System

Type (single, single with cross-over, dual, other)		single w/120 in ³ conv. & air inj.	
Muffler no. & type (reverse flow, straight through separate resonator) Material & mass [kg. (weight lbs.)]		one reverse flow stainless steel 4.67(10.3)	
Resonator no. & type none		one straight through	
Exhaust pipe	Branch o. d., wall thickness	50.8 x 1.4 (2.00 x 0.055)	
	Main o. d., wall thickness	47.8 x 1.4 (1.88 x 0.055)	
	Material & mass [kg. (weight lbs.)]	stainless steel 5.30(11.7)(b)	stainless steel 5.30(11.7)(c)
Intermed- iate pipe	o. d., & wall thickness	47.8 x 1.4 (1.88 x 0.047)	
	Material & mass [kg. (weight lbs.)]	stainless steel 2.36(5.2)	stainless steel 4.17 (9.2)
Tail pipe	o. d., & wall thickness	47.8 x 1.2 (1.88 x 0.047)	
	Material & mass [kg. (weight lbs.)]	stainless steel (see muffler assembly)	

(a) aspirator, exhaust gas recirculation, engine modifications, catalytic converter

(b) Includes 1.56 kg.(3.44 lbs.) - Federal, 1.69 kg.(3.72 lbs.) - California, substrate and stainless steel mesh

(c) Includes 1.69 kg.(3.72 lbs.) substrate and stainless steel mesh

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•) _____

Engine Description/Carb.
 Engine Code

2.2L (135.0 in³) EFI EDF	2.5L (135.0 in³) EFI, EDM
--	---

Transmissions/Transaxle

Manual 3-speed (std., opt., n.a.) (mfr.)	N.A.
Manual 4-speed (std., opt., n.a.) (mfr.)	N.A.
Manual 5-speed (std., opt., n.a.) (mfr.)	standard (CHRYSLER)
Manual overdrive (std., opt., n.a.) (mfr.)	N.A.
Automatic (std., opt., n.a.) (mfr.)	optional (CHRYSLER)
Automatic overdrive (std., opt., n.a.) (mfr.)	N.A.

Manual Transmissions/Transaxle

Number of forward speeds		5
Transmission ratios	In first	3.29
	In second	2.08
	In third	1.45
	In fourth	1.04
	In fifth	0.72
	In overdrive	--
	In reverse	3.14
Synchronous meshing (specify gears)		all forward gears
Shift lever location		floor
Lubricant	Capacity [L(pt.)]	2.3L (4.81 pt.)
	Type recommended	API SF/CC
	SAE viscosity number	SAE 5W-30
	Summer	SAE 5W-30
	Winter	SAE 5W-30
	Extreme cold	SAE 5W-30

Clutch (Manual Transmission)

Make, type, engagement (describe) - (hydraulic, cable, rod)		Luk, dry disc cable	Fichtel and Sachs, dry disc cable
Assist (yes, no/percent)		no	
Type pressure plate springs		belleville	
Total spring load [N(lb.)]		4400 (989)	4700 (1057)
No. of clutch driven discs		one	
Clutch facing	Material	woven asbestos	
	Manufacturer	Textar	
	Part Number	A302297201	181862101001
	Rivets/Plate	16	
	Rivet Size	9.50 (0.374)	9.5 (.374)
	Outside & inside diameter	215 x 154 (8.46 x 6.06)	228 x 150 (8.98 x 5.91)
	Total eff. area [cm ² (in ²)]	353.6 (54.8)	438.0 (67.9)
	Thickness	3.45 (0.136)	3.5 (0.138)
	Engagement cushion method	wave spring segments	
Release Bearing	Type & method of lubrication	angular contact ball bearing, permanently lubed with grease	
Torsional Damping	Method: springs, frictional material	coil springs and fiber friction washers	

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•) _____

Engine Description/Carb.

Engine Code

2.2L (135.0 in³) 2bbl., EDE	2.5L (153.0 in³) EFI, EDM
---	---

Automatic Transmission/Transaxle

Trade Name		Torqueflite
Type and special features (describe)		Torque Converter with Automatically Operated Planetary Transmission and Parallel Axis Final Drive
Selector	Location	Floor or Column Mounted
	Ltr./No. designation	PRND21
Gear ratios	R	2.10
	D	2.69, 1.55, 1.00
	L ₁	-
	L ₂	2.69, 1.55
	L ₃	2.69
Max. upshift speed - drive range [km/h (mph)]		113 (70)
Max. kickdown speed - drive range [km/h (mph)]		105 (65)
Min. overdrive speed [km/h (mph)]		-
Torque converter	Number of elements	Three
	Max. ratio at stall	2.00:1
	Type of cooling (air, liquid)	Liquid
	Nominal diameter	241 (9.5)
Lubricant	Capacity [refill L (pt.)]	8.40 (17.75) (a)
	Type recommended	Mopar ATF Plus (Auto. Trans. Fluid - Type 7176) (b)
Oil cooler (std., opt., NA, internal, external, air, liquid)		Std. Internal liquid

Axle or Front Wheel Drive Unit

Type (front, rear)		Front
Description		Transaxle
Limited slip differential (type)		N.A.
Drive pinion offset		-
Drive pinion (type)		Helical
No. of differential pinions		Two
Pinion/differential adjustment (shim, other)		-
Pinion/differential bearing adjustment (shim, other)		Shim
Driving wheel bearing (type)		Double Row Ball
Lubricant	Capacity [L (pt.)]	see transaxle
	Type recommended	see transaxle
	SAE viscosity number	Summer
		Winter
		Extreme cold

Axle or Transaxle Ratio and Tooth Combinations (See 'Power Teams' for axle ratio usage.)

Axle ratio (or overall top gear ratio)		2.51	2.78	3.02	3.22
No. of teeth	Pinion	14	20	21	20
	Ring gear or gear	49	61	60	61
Ring gear o.d.		197.46 (7.77)	184.53 (7.26)	187.40 (7.38)	187.40 (7.38)
Transaxle	Transfer gear ratio	-	0.91	1.06	1.06
	Final drive ratio	3.50	3.05	2.86	3.05

(a) Torque Converter, Transmission, and Differential

(b) Dexron II may be used, only if Mopar ATF is not available.

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (●)

Engine Description/Carb.
 Engine Code

2.2L (135.0 in.³)
EFI, EDF

2.5L (153.0 in.³)
EFI, EDM

Axle Shafts - Front Wheel Drive

Number used		Two	
Type (straight, solid bar, tubular, etc.)		Solid bar	
		Tube	
Outer diam. x length* x wall thickness	Manual transmission	Left	(a)
		Right	n.a.
	Automatic transmission	Left	(b)
		Right	n.a.
	Optional transmission	Left	(a)
		Right	(c)
	Left	(b)	
	Right	(d)	
Slip Yoke	Type	-	
	Number of teeth	-	
	Spline o.d.	-	
Universal joints	Make and mfg. no.	Inner	(e)
		Outer	GKN-Eur: GI72 or Citroen or SSG #19
	Number used	Two	
		Type, size, plunge	Tripod plunge
	Attach (u-bolt, clamp, etc.)	Rzeppa-fixed	
		-	
	Bearing	Type (plain, anti-friction)	-
		Lubrication (fitting, prepack)	Prepack
Drive taken through (torque tube, arms or springs)		-	
Torque taken through (torque tube, arms or springs)		-	

*Centerline to centerline of universal joints, or to centerline of attachment

- (a) GKN-US: 24.2 x 333.2 (0.95 x 13.12) or Citroen: 22.9 x 333.3 (0.90 x 13.12) or SSG: 23.9 x 327.5 (0.94 x 12.89) or GKN-Eur 22.9 x 334.5 (0.90 x 13.17)
- (b) GKN-Eur: 40.5 x 600.8 x 2.7 (1.59 x 23.65 x 0.10) or GKN-US: 40.5 x 603.3 x 3.72 (1.59 x 23.75 x 0.146) or Citroen: 40 x 598.3 x 3.2 (1.57 x 23.56 x 0.126) or SSG: 38.0 x 591.1 x 5.0 (1.50 x 23.27 x 0.197)
- (c) Citroen: 22.9 x 333 (0.90 x 13.1) or GKN-Eur: 22.9 x 331.4 (0.90 x 13.05) or SSG: 23.9 x 327.5 (0.94 x 12.98)
- (d) Citroen 40 x 598.3 x 3.2 (1.57 x 23.56 x 0.126) or GKN-Eur: 40.5 x 600.8 x 2.7 (1.59 x 23.65 x 0.106) or SSG: 38.0 x 591.1 x 5.0 (1.50 x 23.27 x 0.197)
- (e) GKN-Eur: GI69 or Citroen or GKN-US C-2000 or SSG #19
- (f) GKN-Eur: 92 AC or Citroen or GKN-US C-2000 or SSG #23
- (g) GKN-Eur: 95AC or Citroen or SSG #23

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•) _____

Body Type And/Or
 Engine Displacement

Standard SDA

Heavy Duty SDB

Fleet SDD

Suspension - General

Car leveling	Std./opt./n.a.	N.A.	
	Type (air, hyd., etc.)	-	
	Manual/auto controlled	-	
Provision for brake dip control		Inclined Control Arm and Strut	
Provision for accel. squat control		None	
Provisions for car jacking		Scissors-Type Sill Jack Jack Supports Located at Each End of Body Sills	
Shock absorber (front & rear)	Type	Direct-Hydraulic	Front & Rear: Gas Charged
	Make	Front: , Delco or Monroe;	Rear: Delco, Monroe or Maremont
	Piston diameter	Front: 32 (1.26); Rear: 25.4 (1.0)	Front: 32 (1.26); Rear: 30.2 (1.19)
	Rod diameter	Front: 20 (0.79)	Rear: 12.7 (0.50)

Suspension - Front

Type and description		Iso-Strut	
Drive and torque taken through		Lower control arm	
Travel	Full jounce	68 (2.68)	75 (2.93)
	Full rebound	106.2 (4.18)	99 (3.87)
Spring	Type (coil, leaf, other) & mat'l.	coil, AISI 5160H Chromium Steel	
	Insulators (type & material)	Compression: Rubber	
	Size (coil design height & i.d. bar length x dia.)	229 x 152 I.D. (9.00 x 6.00 I.D.)	
	Spring rate [N/mm (lb./in.)]	14.9 (85)	21.0 (120)
	Rate at wheel [N/mm (lb./in.)]	18.4 (105)	24.0 (140)
Stabilizer	Type (link, linkless, frameless)	Linkless	
	Material & bar diameter	A101 1090 Spring steel.	
		25.4 (1.00).	27.0 (1.06).

Suspension - Rear

Type and description		Trailing Flex Arm with Track Bar	
Drive and torque taken through		Arm	
Travel	Full jounce*	123.0 (4.84)	
	Full rebound	75.5 (2.97)	
Spring	Type (coil, leaf, other) & mat'l.	Coil; AISI 5160H Chromium Alloy Steel	
	Size (length x width, coil design height & i.d., bar length x dia.)	229 x 102 I.D. (9.0 x 4.01 I.D.)	
	Spring rate [N/mm (lb./in.)]	28 (160)	35 (200)
	Rate at wheel [N/mm (lb./in.)]	17.8 (102)	22 (126)
	Insulators (type & material)	Compression: Rubber	
	If leaf	-	
Stabilizer	Type (link, linkless, frameless)	Frameless ERW Tube	
	Material & bar diameter	80KSI HSLA Steel: 25.4 (1.0) O.D.	
Track bar (type)		Channel type	

*from curb

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•)

Body Type And/Or
 Engine Displacement

ALL

Brakes - Service

Description			four-wheel hydraulic actuated system	
Brake type (std., opt., n.a.)		Front (disc or drum)	disc	
		Rear (disc or drum)	drum	
Self-adjusting (std., opt., n.a.)			standard	
Special valving	Type (proportion, delay, metering, other)		dual proportioning valve	
Power brake (std., opt., n.a.)			standard	
Booster type (remote, integral, vac., hyd., etc.)			vacuum, single or tandem	
Vacuum source (inline, pump, etc.)			intake manifold	
Vacuum reservoir (volume in. ³)			--	
Vacuum pump-type (elec. gear driven, belt driven, if other so state)			--	
Anti-skid device type (std., opt., n.a.) (F/R)			N. A.	
Effective area [cm ² (in. ²)]* (F/R)			391 (60.6)	
Gross lining area [cm ² (in. ²)]** (F/R)			406.10 (62.95)	
Swept area[cm ² (in. ²)]*** (F/R)			1349.32 (209.15)	
Rotor	Outer working diameter	F/R	front: 235.7 (9.28)	
	Inner working diameter	F/R	front: 159.7 (6.29)	
	Thickness	F/R	front: 24.0 (0.945)	
	Material & type (vented/solid)	F/R	front: damped cast iron, vented	
Drum	Diameter & width	F/R	rear: 200 (7.87) × 37.62 (1.48)	
	Type and material	F/R	rear: cast composite	
Wheel cylinder bore			front: 54 (2.13); rear: 15.87 (0.625)	
Master cylinder	Bore/stroke	F/R	21.0 (0.827)/32.79 (1.291)	
Pedal arc ratio			all: 3.28:1	
Line pressure at 445 N(100 lb.) pedal load [kPa (psi)]			power: 9854 (1390)	
Lining clearance		F/R	no major adjustments	
Brake Lining	Front wheel (a)	Bonded or riveted (rivets/seq.)		bonded
		Rivet size		--
		Manufacturer		Chrysler
		Lining code *****		CW - K -FF
		Material		molded metallic
		****	Primary or out-board	3700 × 12.45 (5.74 × 0.490)
		Size	Secondary or in-board	3700 × 12.45 (5.74 × 0.490)
		Shoe thickness (no lining)		5.30 (0.209)
	Rear wheel	Bonded or riveted (rivets/seq.)		riveted, 10/shoe
		Manufacturer		Bendix
		Lining code *****		--
		Material		rolled asbestos
		****	Primary or out-board	198.56 × 32.5 × 6.65 (7.82 × 1.28 × 0.262)
		Size	Secondary or in-board	198.56 × 32.5 × 6.65 (7.82 × 1.28 × 0.262)
		Shoe thickness (no lining)		2.17 (0.0854)

* Excludes rivet holes, grooves, chamfers, etc.

** Includes rivet holes, grooves, chamfers, etc.

*** Total swept area for brakes. (Drum brake: Widest lining contact width for each brake x its contact circumference.)

(Disc brake: Square of Outer Working Dia. minus Square of inner Working Dia. multiplied by Pi/2 for each brake.)

**** Size for drum brakes includes length x width x thickness.

***** Manufacturer I.D., catalog or formulation designation and coefficient of friction classification.

(a) area x thickness

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised (●)

Body Type And/Or
 Displacement

ALL

Tires and Wheels (Standard)

Tires	Size (load range)		P175/80 R 13, SL
	Type (bias, radial, etc.)		Steel Radial
	Inflation pressure (cold) for recommended max. vehicle load	Front [kPa (psi)]	240 (35)
		Rear [kPa (psi)]	240 (35)
	Rev./mile - at 70 km/h (45 mph)		870
Wheels	Type & material		steel disc
	Rim (size & flange type)		13 x 5.0 JB
	Wheel offset		40 (1.6)
	Attachment	Type (bolt or stud)	Stud
		Circle diameter	100 (3.94)
		Number & size	5-M 12 x 1.5mm
Spare	Tire and wheel (same, if other describe)		T115/70 D14 Compact Spare 14 x 4.0 T Steel Disc Wheel
	Storage position & location (describe)		Sedan: Vertical, Back of Rear Seat, Passenger Side Station Wagon: Horizontal, Below Cargo Floor

Tires and Wheels (Optional)

Size (load range)		P185/70 R 14, SL
Type (bias, radial, etc.)		Steel Radial
Wheel (type & material)		steel disc or cast aluminum
Rim (size, flange type and offset)		14 x 5.5 JJ 40 (1.6)
Size (load range)		P185/70 R 14, SL
Type (bias, radial, etc.)		
Wheel (type & material)		
Rim (size, flange type and offset)		
Size (load range, ply)		
Type (bias, radial, etc.)		
Wheel (type & material)		
Rim (size, flange type and offset)		
Size (load range, ply)		
Type (bias, radial, etc.)		
Wheel (type & material)		
Rim (size, flange type and offset)		
Spare tire and wheel (if configuration is different than road tire or wheel, describe optional spare tire and/or wheel location & storage position)		Same as Road Tire Sedan: Horizontal - Rear Floor Pan, below Cargo Floor

Brakes - Parking

Type of control		Foot Operated Pedal, Hand Release Lever
Location of control		Lower Left End of Instrument Panel
Operates on		Rear Wheels
If separate from service brakes	Type (internal or external)	--
	Drum diameter	--
	Lining size (length x width x thickness)	--

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•) _____

Body Type And/Or
 Engine Displacement

ALL

Steering Manual (std., opt., n.a.)

Manual (std., opt., n.a.)				standard	
Power (std., opt., n.a.)				optional	
Adjustable steering wheel (tilt, swing, other)		Type and description		tilt	
		(Std., opt., n.a.)		optional	
Wheel diameter (W9) SAE J1100		Manual		381 (15)	
		Power		381 (15)	
Turning diameter m (ft.)	Outside front	Wall to wall (l. & r.)		11.6 (38.1)	
		Curb to curb (l. & r.)		10.7 (35.2)	
	Inside rear	Wall to wall (l. & r.)		6.0 (19.8)	
		Curb to curb (l. & r.)		6.1 (20.1)	
Scrub Radius*				-9 (-0.35)	
Manual	Gear	Type		rack and pinion	
		Make		Cam Gears	
		Ratios	Gear	--	
			Overall	22:1	
	No. wheel turns (stop to stop)		4		
Power	Type (coaxial, linkage, etc.)		integral power unit		
	Make		TRW		
	Gear	Type	rack and pinion with integral power unit		
		Ratios	Gear	--	
			Overall	18.3:1	
	Pump (drive)		pulley and belt, off crankshaft		
	No. wheel turns (stop to stop)		3.2		
Linkage	Type		rack and pinion (rod and ball directly attached to gear)		
	Location (front or rear of wheels, other)		rear of wheels		
	Tie rods (one or two)		2 (tie rod inners integral with rack and pinion gear)		
Steering Axis	Inclination at camber (deg.)		13.3		
	Bearings (type)	Upper	ball bearing		
		Lower	ball joint		
		Thrust	ball bearing		
Steering spindle & joint type				Iso-Strut with lower ball joint	
Wheel spindle	Diameter	Inner bearing		76/42 (3.0/1.65) dia.; 37/40 (1.46/1.57) wide	
		Outer bearing		--	
	Thread (size)		M22 x 1.5		
	Bearing (type)		double row Unipack ball or tapered roller bearing		

*The horizontal distance in the front elevation between wheel centerline and kingpin (ball joint) axis at ground.

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised (•)

Body Type And/Or
 Engine Displacement

All

Wheel Alignment

Front wheel at curb mass (wt.)	Service checking	Caster (deg.)	-
		Camber (deg.)	-0.2° to +0.8°
		Toe-in (deg.)	0.4° Toe-in to 0.2° Toe-out
	Service reset*	Caster	Not adjustable
		Camber	Same as above
		Toe-in	Same as above
	Periodic M.V. inspection	Caster	-
		Camber	-
		Toe-in	-
Rear wheel at curb mass (wt.)	Service checking	Camber	-1.3° to +0.3°
		Toe-in [outside track-mm (in.)]	0.6° Toe-out to 0.6° Toe-in (b)
	Service reset*	Camber	Same as above (shim)
		Toe-in	Same as above (shim)
	Periodic M.V. inspection	Camber	-
		Toe-in	-

* Indicates pre-set, adjustable, trend set or other

Electrical - Instruments and Equipment

Standard Cluster

Certified Cluster (a)

Speedometer	Type	Magnetic torque drive	
	Trip odometer (std., opt., n.a.)	Standard	
EGR maintenance indicator		-	
Charge indicator	Type	Voltmeter	
	Warning device	-	
Temp. Indicator	Type	Magnetic gage	
	Warning device	-	
Oil pressure indicator	Type	Light	Magnetic gage
	Warning device	-	Light
Fuel indicator	Type	Magnetic gage	
	Warning device	-	
Wind shield wiper	Type (standard)	Electric 2-speed, Non-depressed park	
	Type (optional)	Electric 2-speed, Intermittent wipe	
	Blade length	406.4 (16)	
	Swept area (cm ² (in. ²))	5413 (839)	
Windshield washer	Type (standard)	Electric (arm mounted)	
	Type (optional)	-	
	Fluid level indicator	Optional	
Horn	Type mm (in.)	102 mm (4.0 in.) seashell	
	Number used	1 or 2 (low note - Std)	
Other			

(a) Police package

(b) Measurements are measured in degrees, not mm (in.)

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised (•)

Engine Description/Carb.
 Engine Code

2.2L (135.0 in.³)	2.5L (153.0 in.³)
EFI, EDF	EFI, EDM

Electrical - Supply System

Battery	Make	Mopar	
	Model, std., (opt.)	Group 26 (Group 34)	Group 34
	Voltage	12V	
	Amps at 0°F cold crank	335(500)	400(500)
	Minutes-reserve capacity	62 (110)	100(110)
	Amp/hr. - 20 hr. rate	42 (66)	60 (66)
	Location	Left front fender side shield	
Alternator	Manufacturer	Chrysler or Robert Bosch	
	Rating	90 Amp	
	Ratio (alt. crank/rev.)	2.4:1	
	Optional (type & rating)	-	
Regulator	Type	(a)	

Electrical - Starting System

Start, motor	Current drain at 0°F	210-250A	230-280 A
Motor drive	Engagement type	Solenoid shift	
	Pinion engages from (front, rear)	Front	

Electrical - Ignition System

Type	Electronic (std., opt., n.a.)	n.a.		
	Other (specify)	(a)		
Coil	Make	UTC	Prestolite	Diamond
	Model	5226865	5227372	5227252
	Current	Engine stopped - A		
		3.0A		
Spark plug	Engine idling - A	1.9A		
		Champion		
	Make	RN12YC		
	Model	14 mm		
	Thread (mm)	28 (20)		
	Tightening torque (N-m (lb-ft))	0.9 (0.035)		
Distributor	Gap	one		
	Number per cylinder	Chrysler		
	Make	5226575		
	Model	5226575		

Electrical - Suppression

Locations & type	
------------------	--

(a) Engine control computer with electronic spark advance and voltage regulator

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised(•)

Body Type

21, 41

45

Body

Structure

Bumper system
front - rear

Front - Urethane Fascia 4.2 kg. (9.25 lbs.)
Steel 9.8 kg. (21.6 lbs.)

Rear - Urethane Fascia
4.05 kg. (8.9 lbs.)
Steel 7.39 kg. (16.25 lbs.)

Rear - Urethane Fascia
3.5 kg. (7.6 lbs.)
Steel 5.7 kg. (12.5 lbs.)

Anti - corrosion treatment

Extensive use of galvanized steel

Body - Miscellaneous Information

Type of finish (lacquer, enamel, other)

Buffable acrylic enamel

Hood

Hinge location (front, rear)

Rear

Type (counterbalance, prop)

Counterbalanced, clockspring

Release control (internal, external)

Internal

Trunk-
lid

Type (counterbalance, other)

Counterbalanced, Torsion bar

Internal release control (elec., mech., n.a.)

--

Hatch-
back lid

Type (counterbalance, other)

Gas Prop

Internal release control (elec., mech., n.a.)

--

Station
Wagon

Vent window control (crank,
friction, pivot, power)

Front

None

Rear

None

Seat cushion type
(e.g., 60/40, bucket, bench,
wire, foam, etc.)

Front

Bucket - Flex-O-Lator Mat

Rear

Full foam with zig zag helper elements

3rd seat

--

Seat back type
(e.g., 60/40, bucket, bench,
wire, foam, etc.)

Front

Bucket - Flex-O-Lator Mat

Rear

Formed wire

3rd seat

--

MVMA Specifications Form
Passenger Car
METRIC (U.S. Customary)

Car Line DODGE ARIES
 Model Year 1987 Issued 6-20-86 Revised (•) _____

Body Type

21	41	45
----	----	----

Restraint System

Active restraint system	Standard/optional	Standard		
	Type and description	Front: Outboard lap and shoulder belt Rear: Lap belt		
	Location	Front: two Rear: three		
Passive seat belts	Standard/optional	-		
	Power/manual	-		
	2 or 3 Point	-		
	Knee bar/lap belt	-		

Frame

Type and description (separate frame, unitized frame, partially unitized frame)		Unitized construction		
Glass	SAE Ref. No.			
Windshield glass exposed surface area [cm ² (in ²)]	S1	8069 (1251)		
Side glass exposed surface area [cm ² (in ²)]	S2	9227 (1430)	9647(1495)	15542(2409)
Backlight glass exposed surface area [cm ² (in ²)]	S3	4559 (707)	5139 (797)	5234 (811)
Total glass exposed surface area [cm ² (in ²)]	S4	21855 (3388)	22855(3543)	28845(4471)
Windshield glass (type)		Laminated safety glass		
Side glass (type)		Heat treated safety glass		
Backlight glass (type)		Heat treated safety glass		

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised(•)

Body Type

All

Convenience Equipment (standard, optional, n.a.)

Air conditioning (manual, auto, temp. control)		Manual - Opt.
Clock (digital, analog)		Digital - Std. with radio
Compass/thermometer		N.A.
Console (floor, overhead)		Full Floor - Opt. Mini - Std.
Defroster, elec. backlight		EBL - Opt.
Electronic	Diagnostic warning (integrated, individual)	N.A.
	Instrument cluster (list instruments)	N.A.
	Keyless entry	N.A.
	Tripminder (avg. spd. fuel)	N.A.
	Voice alert (list items)	N.A.
	Other	
Fuel door lock (remote, key, electric)		N.A.
Lamps	Auto head on/off delay, dimming	N.A.
	Cornering	N.A.
	Courtesy (map reading)	Std. - Medium
	Door lock, ignition	Ignition - Opt.
	Engine compartment	Opt.
	Fog	N.A.
	Glove compartment	Std. - Medium
	Trunk	Std. - Medium
	Other	Dome - Std.
	Shift indicator	Std. N.A. with automatic
Mirrors	Day/night (auto. man.)	Manual - Std.
	L.H. (remote, power, heated)	Remote - Std - Medium. Opt. - Low
	R.H. (convex, remote, power, heated)	Opt. - All
	Visor vanity (RH/LH, illuminated)	RH w/ visor vanity - Std. - Medium
Parking brake - auto release (warning light)		Std.
Power equipment	Door locks/ deck lid - specify	Door locks - Opt.
	Seat (2-4-6 way)	
	heated (driver, pass., other)	N.A.
	lumbar, hip, thigh support (power, manual)	
	reclining (driver, pass.)	
	memory (1-2 preset, recline)	
	Side windows	N.A.
Radio Systems	Vent windows	N.A.
	Rear windows	N.A.
	Antenna (location, whip, w/shield, power)	Whip - Std. - Right front fender
	AM, FM, stereo, tape, CB	Am Electronically Tuned Radio - Std. - Medium Opt - Low
Speaker (number, location) Premium sound		N.A.
Roof open air/ fixed (flip-up, sliding, "T")		N.A.
Speed control device		Opt.
Speed warning device (light, buzzer, etc.)		N.A.
Tachometer (rpm)		N.A.
Telephone system - mobile		N.A.
Theft protection-type		Inside Hood Release-Std. Glove Box Lock-Std. Locking Steering Column-Std. Anti-theft Labels-Std.

MVMA Specifications Form

Passenger car

METRIC (U.S. Customary)

Cae and Body Dimensions

Car Line **DODGE ARIES**Model Year **1987**Issued **6-20-86**

Revised(•)

See Key Sheets for Definitions

All dimensions to ground are for comparative purposes only. Dimensions are to be shown for all base body models of each car line

SAE Ref. no. refers to the definition published in SAE Recommended Practice J1100 "Motor Vehicle Dimensions", unless otherwise specified.

Body Type	SAE Ref. No.	21	41	45
Width				
Tread (front)	W101		1462 (57.6)	
Tread (rear)	W102		1453 (57.2)	
Vehicle width	W103		1727 (68.0)	
Body width at SgRP (front)	W117		1725 (67.9)	
Vehicle width (front doors open)	W120	4019 (158.2)		3431 (135.1)
Vehicle width (rear doors open)	W121		3142 (123.7)	
Front fender overall width	W106		1709 (67.3)	
Rear fender overall width	W107		1727 (68.0)	
Tumble-home (deg.)	W122		23°	

Length

Wheelbase	L101	2548 (100.3)	2550 (100.4)
Vehicle length	L103	4537 (178.6)	4533 (178.5)
Overhang (front)	L104	985 (38.8)	
Overhang (rear)	L105	1004 (39.5)	998 (39.3)
Upper structure length	L123	2937 (115.6)	
Rear wheel C/L "X" coordinate	L127	2636 (103.8)	2638 (103.9)
Cowl point "X" coordinate	L125	535 (21.1)	
Front end length at centerline	L126	1432 (56.4)	
Rear end length at centerline	L129	887 (34.9)	164 (6.5)

Height*

Passenger distribution (front/rear)	PD 1,2,3	2 - Front 3 - Rear	
Trunk/cargo load		--	
Vehicle height	H101	1333 (52.5)	1351 (53.2)
Cowl point to ground	H114	912 (35.9)	913 (35.9)
Deck point to ground	H138	887 (34.9)	858 (33.8)
Rocker panel front to ground	H112	206 (8.1)	
Bottom of door closed front to ground	H133	251 (9.9)	257 (10.1)
Rocker panel rear to ground	H111	178 (7.0)	
Bottom of door closed rear to ground	H135	--	246 (9.7)
Windshield slope angle	H122	53°	
Backlight slope angle	H121	32°	34°

Ground Clearance

Front bumper to ground	H102	299 (11.8)	
Rear bumper to ground	H104	274 (10.8)	294 (11.6)
Bumper to ground (front at curb mass (wt.))	H103	318 (12.5)	314 (12.4)
Bumper to ground (rear at curb mass (wt.))	H105	356 (14.0)	376 (14.8)
Angle of approach (degrees)	H106	18°	
Angle of departure (degrees)	H107	16°	17°
Ramp breakover angle (degrees)	H147	11°	12°
Axle differential to ground (front/rear)	H153	N.A.	
Min. running ground clearance	H156	117 (4.6)	116 (4.6)
Location of min. run. ground clearance		Frt. Susp. C'mbr. Brkt. (left hand side)	

* All vehicle height and ground clearance are made at the Manufacturer's Design Load Weight unless otherwise noted

Manufacturer's Design Load Weight is defined with indicated passenger distribution and trunk/cargo load.

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)
Cae and Body Dimensions

Car Line **DODGE ARIES**

Model/Year **1987** Issued **6-20-86** Revised(•) _____

See Key Sheets for Definitions

Body Type

SAE Ref. No.	21 Bucket	41 Bucket	45 Bucket
--------------------	--------------	--------------	--------------

Front Compartment

SqRP front, "X" coordinate	L31		1405 (55.3)	
Effective head room	H61	970 (38.2)	980 (38.6)	979 (38.5)
Max. eff. leg room (accelerator)	L34		1072 (42.2)	
SqRP to heel point	H30		264 (104)	
SqRP to heel point	L53		864 (34.0)	
Back angle	L40		24°	
Hip angle	L42		97°	
Knee angle	L44		127°	
Foot angle	L46		87°	
Design H - point front travel	L17		197 (7.8)	
Normal driving & riding seat track trvl.	L23		178 (7.0)	
Shoulder room	W3	1398 (55.0)		1407 (55.4)
Hip room	W5	1416 (55.7)		1412 (55.6)
Upper body opening to ground	H50		1222 (48.1)	
Steering wheel maximum diameter*	W9		381 (15.0)	
Steering wheel angle	H18		26°	
Accel. heel pt. to steering wheel center	L11		511 (20.1)	
Accel. heel pt. to steering wheel center	H17		641 (25.2)	
Steering wheel to C/L of thigh	H13		110 (4.3)	
Steering wheel torso clearance	L7		334 (13.1)	
Headlining to roof panel	H37		15 (0.6)	
Undepressed floor covering thickness	H67		22 (0.9)	

Rear Compartment

SqRP Point couple distance	L50		791 (31.1)	785 (30.9)
Effective head room	H63	940 (37.0)	960 (37.8)	977 (38.5)
Min. effective leg room	L51		913 (35.9)	907 (35.7)
SqRP (second to heel)	H31		281 (11.1)	
Knee clearance	L48		16 (0.6)	10 (0.4)
Compartment room	L3		631 (24.8)	684 (26.9)
Shoulder room	W4	1494 (58.8)		1421 (55.9)
Hip room	W6	1380 (54.3)		1428 (56.2)
Upper body opening to ground	H51	N.A.		1214 (47.8)
Back angle	L41		25°	
Hip angle	L43		86°	
Knee angle	L45		92°	91°
Foot angle	L47		127°	
Headlining to roof panel (second)	H38	14 (0.6)	15 (0.6)	9 (0.4)
Depressed floor covering thickness	H73		13 (0.5)	

Luggage Compartment

Usable luggage capacity [L (cu. ft.)]	V1		424 (15.0)	N.A.
Liftover height	H195		673 (26.5)	503 (19.8)

Interior Volumes (EPA Classification)

Vehicle class (subcompact, compact, etc.)			Mid - size	
Interior volume index (cu. ft.)		111.6	111.2	131.1
Trunk/cargo index (cu. ft.)		424 (15.039)		34.579

* See Page 14

All linear dimensions are in millimeters (inches) unless otherwise noted.

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)
Car and Body Dimensions

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86** Revised(*)

See Key Sheets for Definitions

Body Type

SAE Ref. No.	21, 41	45
--------------	--------	----

Station Wagon - Third Seat

SgRP couple distance	L85	
Shoulder room	W85	
Hip room	W86	
Effective leg room	L86	
Effective head room	H86	
SgRP to heel point	H87	
Knee clearance	L87	
Seat facing direction	SD1	
Back angle	L88	
Hip angle	L89	
Knee angle	L90	
Foot angle	L91	

Station Wagon - Cargo Space

Cargo length (open front)	L200	1747(68.8)
Cargo length (open second)	L201	845 (33.3)
Cargo length (closed front)	L202	1746 (68.7)
Cargo length (closed second)	L203	844 (33.2)
Cargo length at belt (front)	L204	1587 (62.5(a))
Cargo length at belt (second)	L205	815(32.1)
Cargo width (wheelhouse)	W201	980 (38.6)
Rear opening width at floor	W203	1332 (52.4)
Opening width at belt	W204	1317 (51.9)
Max. rear opening width above belt	W205	1000 (39.4)
Cargo height	H201	852 (33.5)
Rear opening height	H202	691 (27.2)
Tailgate to ground height	H250	--
Front seat back to load floor height	H197	480 (18.9) (a)
Cargo volume index [m ³ (ft. ³)]	V2	1.917 (67.7)
Hidden cargo volume [m ³ (ft. ³)]	V4	0.028 (1.0) (b)
Cargo volume index-rear of 2-seat	V10	988 (34.9)

Hatchback - Cargo Space

Cargo length at front seatback height	L208	
Cargo length at floor (second)	L209	
Cargo length at second seatback height	L210	
Cargo length at floor (second)	L211	
Front seatback to load floor height	H197	
Second seatback to load floor height	H198	
Cargo volume index[m ³ (ft. ³)]	V3	
Hidden cargo volume [m ³ (ft. ³)]	V4	
Cargo volume index-rear of 2-seat	V10	

Aerodynamics*

Wheel lip to ground, front	631 (24.8)	
Wheel lip to ground, rear	622 (24.5)	634 (24.96)
Frontal area [m ² (ft. ²) (c)	1.97 (21.2)	2.02 (21.72)
Drag coefficient (Cd)	N.A.	

All linear dimensions are in millimeters(inches) unless otherwise noted
 (a) Top of Head Restraint
 (c) Models 22, 41: All tires, two mirrors, antenna and class II wheel covers
 Model 45: All tires, two mirrors, antenna, luggage rack and class II wheel covers

*EPA Loaded Vehicle Weight, Loading Conditions
 (b) Under Cargo Cover Surface
 Model 27: Two mirrors, antenna and class III wheel covers

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised(*)

Body Type

All

Vehicle Fiducial Marks

Fiducial Mark Number*		Define Coordinate Location
Front		The center of gauge holes located in front longitudinal approximately 836 mm (32.9 in.) from centerline of front wheels.
Rear		The center of gauge holes located in rear longitudinal approximately 3211 mm (126.4 in) from the centerline of front wheels.
Front	W21	433.5 (17.1)
	L54	925 (36.4)
	H81	-9 (-0.35) Bottom surface of Longitudinal
	H161	
	H163	
Rear	W22	527.6 (20.8)
	L55	3452.4 (135.9)
	H82	236 (9.3) Bottom Surface of Longitudinal
	H162	
	H164	

*Reference - SAE Recommended Practice, J182, Motor Vehicle Fiducial Marks.
 All linear dimensions are in millimeters (inches).

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987**

Issued **6-20-86**

Revised(*)

Body Type

21, 41	45
--------	----

Lamps and Headlamps Shape*

Height above ground to center of bulb or marker	Headlamp (SAE - H127)	Highest**	677.4 (26.7)	
		Lowest	--	
	Taillamp (SAE - H128)	Highest**	672.9 (26.5)	758.0 (29.8)
		Lowest	--	
	Sidemarker	Front	677.4 (26.7)	
		Rear	332.5 (13.1)	758.0 (29.8)
Distance from centerline of car to center of bulb or marker	Headlamp	Inside	--	
		Outside**	554.0 (21.8)	
	Taillamp	Inside	--	
		Outside**	569.2 (22.4)	774.0 (30.5)
	Directional	Front	751.0 (29.6)	
		Rear	569.2 (22.4)	777.0 (30.6)

Halogen headlamp (std., opt., n.a.)	Lo beam	Standard
	Hi beam	Standard
	Replaceable bulb	N.A.
	Shape	Rectangular
Headlamp other than above	Lo beam	--
	Hi beam	--
	Replaceable bulb	--
	Shape	--
	Type	--

* Measured at curb mass (weight)

** If single lamps are used enter here.

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**

Model Year **1987** Issued **6-20-86** Revised()

Estimated

	Vehicle Mass (Weight)							
Model	CURB MASS, kg (weight, lb.)*			% PASS. MASS DISTRIBUTION				SHIPPING MASS, kg (weight, lb.)**
	Front	Rear	Total	Pass. in Front		Pass. in Rear		
				Front	Rear	Front	Rear	
Aries								
2.2L (135.0 in.3) EDF engine								
Two door - sedan	678	399	1077	50.2	49.8	19.0	81.0	1047
	(1495)	(880)	(2375)					(2309)
Four door - sedan	680	410	1090	50.2	49.8	19.0	81.0	1060
	(1499)	(903)	(2402)					(2336)
Aries LE								
2.2L (135.0 in.3) EDF engine								
Two door - sedan	683	404	1087	50.2	49.8	19.0	81.0	1057
	(1505)	(891)	(2396)					(2330)
Four door - sedan	684	415	1099	50.2	49.8	19.0	81.0	1069
	(1507)	(915)	(2422)					(2356)
Station Wagon	678	447	1125	50.2	49.8	19.0	81.0	1095
	(1495)	(985)	(2480)					(2414)

* Reference - SAE J1100 Motor vehicle dimensions, curb weight definition.

** Shipping mass (weight) definition-

MVMA Specifications Form
Passenger car
METRIC (U.S. Customary)

Car Line **DODGE ARIES**
 Model Year **1987** Issued **6-20-86** Revised(*)

Estimated

Optional Equipment Differential Mass (Weight)*

Equipment	MASS, kg (weight, lb.)			Remarks
	Front	Rear	Total	
2.5L (153.0 in. ³) EDM	42 (93)	-2 (-5)	40 (88)	LE only and auto. trans.
Automatic transmission	18 (41)	-1 (-3)	17 (38)	
Air conditioning	26.8 (59)	-2.3 (-5)	24.5 (54)	
Power steering	9.1 (20)	0.4 (1)	9.5 (21)	
Power door locks	1.4 (3)	0.4 (1)	1.8 (4)	two - door
	2.3 (5)	1.3 (3)	3.6 (8)	four - door and station wagon
Bench seat	4.1 (9)	5.0 (11)	9.1 (20)	LE two door, automatic trans. only
	3.6 (8)	4.1 (9)	7.7 (17)	LE four door and station wagon automatic transmission only
Console	1.4 (3)	1.4 (3)	2.8 (6)	
AM Stereo/FM Stereo radio	1.7 (4)	2.3 (5)	4.0 (9)	Aries
	0.4 (1)	1.4 (3)	1.8 (4)	Aries LE
500 ampere battery	5.9 (13)	-0.9 (-2)	5.0 (11)	
Rear wiper washer	-0.9 (-2)	4.5 (10)	3.6 (8)	Station wagon only
Luggage rack	0.4 (1)	5.0 (11)	5.4 (12)	Station wagon only
Special sound insulation	0.4 (1)	2.3 (5)	2.7 (6)	Sedan
	0 (0)	10.9 (24)	10.9 (24)	Station wagon
Front & rear floor mats	2 (4)	1 (3)	3 (7)	
Tonneau cover	0 (0)	2.3 (5)	2.3 (5)	Station wagon
Conventional spare tire	-7 (-15)	15 (32)	8 (17)	Sedan
	5 (11)	11 (24)	6 (14)	Station wagon
Undercoating	0.9 (2)	1.4 (3)	2.3 (5)	

* Also see Engine - General for dressed engine mass (weight).